

Flexwall 2700

FLEXURA

General specifications

Type of product	Veneered wall panel	
Wood specie	European oak	
Grading	AB mix match (Crown / Half Crown / Quarter rift)	
Pattern	Interior wall panel	
Finish	Elastic varnish program	
Staining	Water based color	
Thickness of the top layer	0.6 mm	0.024 in
Core	MDF	
Click System	Flexura Click System	

Technical information

Formaldehyde emission EN12460-3	E1	
Content of PCP	<5 ppm	
Falling sand	>2000 cycles	
Scratch test**	1	
Gloss level	Ultra matt 5	
Cross hatch adhesion (cross cut test)**	1	

** (1 is best – 5 is worst)

Size and packaging information

Length	2700 mm	106.30 in
Width	600 mm net	23.62 in
Total thickness	11.2 mm	0.44 in
Quantity per carton	2 pcs	
M ² per carton	3.24 m ²	34.88 ft ²
M ² per full pallet	97.20 m ²	1046.25 ft ²
Cartons per full pallet	30	
Weight per box	28 kg	61.73 lbs
Weight per pallet	840 kg	1851.88 lbs
Pallet size	2750 x 630 x 1100 mm	108.27 x 24.80 x 43.31 in



Certificates

FSC

On request

FSC® MIX C159816



Flexura Floors & Panels

Schoendalestraat 306 | B-8792 Waregem |
+32 54 73 91 35 | info@flexura.be

