

DuroForm Mesh+

EN 314 Part 2 Class 3 | FSC® Certified

Available from stock in 9mm, 12mm, 15mm and 18mm, our DuroForm Mesh+ panel is an excellent alternative to traditional Birch plywood phenolic overlaid plywood options. With its multi-lamination core construction and Aica overlay, users of the material can expect a high end finish on this product that's been manufactured with the UK market in mind.

Specification	
Overlay	370gm Aica overlay with grey painted edges and a smooth Aica reverse 185gm
Thickness	9mm, 12mm, 15mm and 18mm available from stock – other thicknesses available on a forward basis
Dimensions	2440mm x 1220mm & 2500mm x 1220mm (18mm brown film only)
Core	Eucalyptus throughout special construction • 9mm = 7 ply • 12mm = 9 ply • 18mm = 13 ply
Properties	Special construction offers improved strength and stability
Performance	Manufactured with a phenolic glue bond throughout, achieving EN 314 Part 2 Class 3 and EN 636-3 end use class ratings
Application	Commercial vehicle, van and trailer flooring, arena seating and steps, access and loading platforms, walkways and ramps, marquee flooring and other interior/exterior applications (once suitably protected)

- ✓ 370gm Mesh pattern
- ✓ Special Eucalyptus Construction
- ✓ EN 636-3

