



Always reliable

Selex Floor TG4

In CMPC we are committed to provide high quality products and offer an excellent service. That is why we developed Selex Floor TG4, the complete solution for floors and roofs.

- ▶ High visual appearance
- ▶ Excellent structural properties
- ▶ Consistent quality
- ▶ Easy to work with
- ▶ Manufactured from sustainable managed forest FSC® certified



* Ask about our FSC® certified products.

Selex Floor TG4

Product benefits and applications

- A multipurpose attractive quality panel specially made for construction.
- Suitable for structural applications such as roofing, flooring and wall sheathing.
- Easy to handle due to its excellent strength to weight ratio.
- Outstanding visual face without open defects and fully sanded on both sides.

Features

	B	C
Finishing		
▶ Sanding grade	150	120
Natural defects		
▶ Sound knots	Up to 25 mm. wide	Up to 40 mm. wide
▶ Unsound knots	Repaired, up to 25 mm. wide	Up to 40 mm. wide
▶ Knot holes	Not allowed	Up to 25 mm. wide
▶ Pitch pockets	Up to 25 mm. wide	Allowed
▶ Bark pockets	Not allowed	Allowed
▶ Freckles	Allowed	Allowed
Machining defects		
▶ Open splits	Up to 1 mm. wide	Up to 25 mm. wide
▶ Open cracks	Up to 1 mm. wide	Up to 25 mm. wide
▶ Fungal stains	Allowed	Allowed
▶ Roughness	Allowed	Allowed
Repairs		
▶ Inner splits in knots	Allowed	Unrepaired, up to 1 mm. wide
▶ Routings with polyurethane	Occasionally	Not applicable
▶ Putty patches	Allowed	Not applicable
▶ Wooden patches	Allowed	Not applicable



General Specifications

Dimensions: 8' x 2' (2.425 x 600 m)	Thickness (mm)	18	22
	Nº of veneers	7	7
Density	▶	480 - 550 kg m ³	
Adhesive	▶	CARB 2 and E1 compliant	
Structural certification	▶	EN 13986-CE2 + (Structural), EN 636-2S, EN314-2 Class 3	
Forestry certification	▶	Manufactured from sustainable managed forest FSC® certified	

📍 CMPC MADERAS S.A.

📍 Agustinas 1343, 4th floor - Santiago de Chile
(56) 22441 2814

✉ woodsales@cmpc.cl ▶ www.cmpcmaderas.cl