

**Declaration of Performance
for product Plywood 3.6mm
HY-Dop-021-015**

1	Identification code :	ALPHAPLY PLYWOOD,FSC 100% EUCALYPTUS FACED, FSC 100% EUCALYPTUS AND FSC 100% POPLAR COMBI CORE 2440*1220*3.6mm
2	Batch-/Serial number	
3	Intendent use:	Internal use as structural components in Humid conditions
4	Harmonized technical specification	EN 13986:2004
5	Manufacturer:	Pizhou Haoyu Wood Co.,Ltd. Xinhua Village, Guanhu Town, Pizhou City, Jiangsu Province, P.R.China
6	System of Assessment and verification of constancy of performance (AVCP)	4
7	Notified body:	APPLUS+
	Certificate N	0370-CPR-2325

8	Declared performance		
Essential characteristics		Performance	Harmonized technical specification
Bending strength parallel (N/mm2)		38	ITT According to EN 310
perpendiculare (N/mm2)		28	
Bending stiffness(Modulus Elasticity) parallel (N/mm2)		5065	
perpendiculare (N/mm2)		4053	
Classiffcation according to EN636		F20/15 E40/25	EN636
Bonding quality		Class 2	ITT(EN314)
Durability (moisture resistance) (N/mm2)		1.01	EN314-1/5.1.2
Moisture Content (Up to 14) (%)		14	EN 322
Density		550	EN 323
Realease of Formaldehyde		E1	ISO 12460-3
Reaction to fire		Declared:D-s2,d0	

The performance of the product(products)is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer,identified above.
Signed for and behalf of the manufactured by:

Signature:	Shi San
Signature Date:	July.5th,2021
Position in the Company:	Quality Manager
Company:	Pizhou Haoyu Wood Co.,Ltd.

Declaration of Performance
for product Plywood 5.5mm
HY-Dop-021-016

1	Identification code :	ALPHAPLY PLYWOOD,FSC 100% EUCALYPTUS FACED, FSC 100% EUCALYPTUS AND FSC 100% POPLAR COMBI CORE 2440*1220*5.5mm
2	Batch-/Serial number	
3	Intendent use:	Internal use as structural components in Humid conditions
4	Harmonized technical specification	EN 13986:2004
5	Manufacturer:	Pizhou Haoyu Wood Co.,Ltd. Xinhua Village, Guanhu Town, Pizhou City, Jiangsu Province, P.R.China
6	System of Assessment and verification of constancy of performance (AVCP)	4
7	Notified boby:	APPLUS+
	Certificate N	0370-CPR-2325

8	Declared performance		
Essential characteristics		Performance	Harmonized technical specification
Bending strength parallel (N/mm2)		46	ITT According to EN 310
perpendiculare (N/mm2)		30.5	
Bending stiffness(Modulus Elasticity) parallel (N/mm2)		5145	
perpendiculare (N/mm2)		4150	
Classiffcation according to EN636		F20/15 E40/25	EN636
Bonding quality		Class 2	ITT(EN314)
Durability (moisture resistance) (N/mm2)		1.01	EN314-1/5.1.2
Moisture Content (Up to 14) (%)		14	EN 322
Density		550	EN 323
Realease of Formaldehyde		E1	ISO 12460-3
Reaction to fire		Declared:D-s2,d0	

The performance of the product(products)is in conformity with the declared performance
This declaration of performance is issued the sole responsibility of the manufacturer,identified above.
Signed for and behalf of the manufactured by:

Signature:	Shi San
Signature Date:	July.5th,2021
Position in the Company:	Quality Manager
Company:	Pizhou Haoyu Wood Co.,Ltd.