



WOOD
INTERNATIONAL
AGENCY

FLAMEBREAK

With door blanks available ex-stock from Wood International Agency Limited, the Flamebreak 430 having undertaken a robust testing regime at UKAS accredited laboratories, the Flamebreak Fire & Security system is now available for Q-Mark certificated timber door fabricators.

When Building Regulations for both fire safety (Part B) and security (Part Q) need to be met, this fully-tested system complies with both requirements, Third-Party Certified under the BM Trada Q-Mark scheme, keeping properties and people, safe and secure.

FIRE & SECURITY DUAL-SCOPE SYSTEM CERTIFIED BY THE BM TRADA Q-MARK SCHEME



Wood International Agency Limited
Wood House, 16 King Edward Road
Brentwood, Essex, CM14 4HL



+44 (0) 1277 232991



doors@woodia.co.uk



www.woodia.co.uk

PRODUCT PERFORMANCE - 30 MINUTES FIRE RESISTANCE & ENHANCED SECURITY

FULL DOOR ASSEMBLY PRIMARY TEST EVIDENCE

ITEM	PARAMETERS
Blank	Flamebreak 430
Max Finished Leaf Size	931mm wide x 2151mm high
Door Frame	Sapele Hardwood Minimum 95x44mm including a 50x15mm rebate
Cill (optional)	Sapele Hardwood Minimum 100x20-50mm including a 50x15mm rebate
Lippings	4 edges Sapele Hardwood 8-13mm thick
Intumescent Seals	Pyroplex 8700 or 8712 15x4mm Fitted centrally in frame reveal and centrally in bottom of leaf
Weatherseal	Schlegel Aquamac 21
Hinges	4 No. NICO 5350R10SEC
Lock	Winkhaus AV2 F2070 (2559 895)
Cylinder	ERA BS-L-T3535-51 (TS007 3*)
Handle	Winkhaus Melbourne
Letter Plate	UAP Soterian (TS008)

