

Product Information - Last Updated in April 2021

Product Code: 5060003111219		Brand: Richmond G416			
1220X2440X9mm FSC Certified Primed Cross Grain V Grooved & Beaded Richmond Profile MR MDF					
This product is suitable for NON - STRUCTURAL use					
Length	1220mm	Width	2440mm	Thickness	9.00mm
Average Density	700.00 kg/m3	Pieces per Pack	40	Volume per Pack	2.1430m3
Service Class		Glue Bond		Formaldehyde Class	E1
Country of Manufacture	UK				
Manufacturer	Matchboard Ltd				
Environmental Status	FSC® MIX CREDIT: CU-COC-805640				
FSC® Product Type	W8.3 (Hardboard/Ins Board/MDF)				
PEFC™ Product Type	Not PEFC Certified				
Product Type	MDF - V-Grooved & Beaded				
Product DOP	The Manufacturer's Declaration of Performance is available on request				

Material Safety Data for Plywood and Wood Based Panels:

Wood-based panels can be bulky and heavy and this needs to be considered when manual handling is performed. Further information can be obtained from the HSE website. <http://www.hse.gov.uk/pubns/indg318.htm>

Machining and processing (cutting or sanding for example) of wood-based panels will produce dust which can cause irritation to eyes and throat. The use of protective goggles and face-masks and suitable dust extraction equipment is therefore recommended. Further information can be obtained from the HSE website. <http://www.hse.gov.uk/woodworking/wooddust.htm>

Wood splinters can cause irritation or infection if they enter the skin - wearing suitable gloves is therefore recommended to protect the hands.

Under certain circumstances the release of small quantities of formaldehyde gas from wood-based panels containing formaldehyde based adhesives can cause irritation of the eyes and throat. Always ensure adequate ventilation is available in areas where products are stored or processed.

All wood-based products are flammable - store them in a cool, dry, well ventilated place away from sources of heat, flames or sparks.