

TREATMENT/CERTIFICATE COLLECTION/DELIVERY NOTE



FireWright
WJ Group

Delivery Note : DEL00918

| | |
|-----------|--------------------------------|
| Customer | International Plywood(Imp) Ltd |
| Date | 18/04/2024 |
| Job No. | /762 |
| No. Packs | 16 |
| Species | Eucalyptus |

| | |
|---------------------|---------------------------------------|
| Customer Ref | LN21/02/24-01 |
| Treatment Code | BURNBLOCK B EUCA |
| Treatment | Burnblock Euro Class B Eucalyptus Ply |
| Total M3 | 42.866 |
| Fire Classification | B-s1,do |

| Number of pieces | Length | Dimensions | Pack No | Cust. Pack No | Charge | M3 | Running Metres |
|------------------|--------|-----------------|---------|---------------|--------|-------|----------------|
| 100 | 2.44 | @ 9.0 X 1220.0 | 1 | 1 | 2990 | 2.679 | 244.00 |
| 75 | 2.44 | @ 12.0 X 1220.0 | 2 | 2 | 2989 | 2.679 | 183.00 |
| 75 | 2.44 | @ 12.0 X 1220.0 | 3 | 3 | 2989 | 2.679 | 183.00 |
| 75 | 2.44 | @ 12.0 X 1220.0 | 4 | 4 | 2989 | 2.679 | 183.00 |
| 36 | 2.44 | @ 25.0 X 1220.0 | 5 | 5 | 2984 | 2.679 | 87.84 |
| 36 | 2.44 | @ 25.0 X 1220.0 | 6 | 6 | 2984 | 2.679 | 87.84 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 7 | 7 | 2972 | 2.679 | 122.00 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 8 | 8 | 2972 | 2.679 | 122.00 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 9 | 9 | 2978 | 2.679 | 122.00 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 10 | 10 | 2978 | 2.679 | 122.00 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 11 | 11 | 2979 | 2.679 | 122.00 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 12 | 12 | 2979 | 2.679 | 122.00 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 13 | 13 | 2984 | 2.679 | 122.00 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 14 | 14 | 2990 | 2.679 | 122.00 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 15 | 15 | 2991 | 2.679 | 122.00 |
| 50 | 2.44 | @ 18.0 X 1220.0 | 16 | 16 | 2991 | 2.679 | 122.00 |

Received By:

Print Name: TOMAS

Date: 22/4/24

Vehicle Reg: EO15 RXT

Signed: [Signature]

(On behalf of WJ Fire Retardant Ltd)

WJ FireWright fire retardant treated material contains Burnblock for the purpose of inhibiting the production of smoke and reducing the spread of flame in the event of a fire. The timber above has been treated by a high-pressure vacuum impregnation process in accordance with European Standard EN 13501-1:2018. Products which require kiln drying post treatment are dried to between 6-15% moisture content. Full guidance on safe and effective use of pressure treated fire retardant timber is contained in the BURNBLOCK safety data sheet, available on request. There is no requirement to use any special safety equipment or protection when handling BURNBLOCK treated timber as it is harmless to the skin and is safe for people to use. Any waster containing the BURNBLOCK treatment can be considered non-hazardous and should be handled in the same way as non-treated timber. There is no evidence of negative effects on the structural strength of treated timber after BURNBLOCK has been applied and it does not induce corrosion. All ingredients found in BURNBLOCK solution occur naturally, as found in nature or in fruits and vegetables in their dissociated form. Wood is a natural product meaning visually identical products may behave differently. Remove plastic packing, stick each layer of treated timber and store in a dry, well-ventilated area. Whilst provisions are taken to minimise stick marks, salt extracts, discolouration, blotches, twisting and warping we cannot guarantee there won't be some alteration to the timber as a result of the treatment process.